



199.00 EUR
incl. 19% VAT, plus [shipping](#)



Support: [Specifications](#)

Compatible CPUs a.o. : R-464L, R-460H, R-272F, R-268D, R-460L, R-452L, R260H, R-252F

- AMD eTrinity Processor (FS1r2 Socket) with A75 FCH (Hudson D3) Chipset
- Support DirectX 11 3D Graphics Acceleration
- Support 6 * Serial ATA3 (6Gb/s) Devices with RAID 0, 1 & 10
- Support SO-DIMM DDR3 1600 Dual Channel up to 16GB
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- Support DP & HDMI Output
- Supports 2 * Realtek RT8111EVL Gigabit LAN
- Support CPU Smart FAN
- Mini-ITX Form Factor(170mm x 170mm)

• CPU	• Support AMD eTrinity Processor (FS1r2 Socket)
• Chipset	• AMD A75 FCH Hudson D3 Chipset
• Memory	• 2 * SODIMM Sockets for un-buffered Dual Channel DDR3 1600 SDRAM up to 16 GB
• Expansion Slots	• 1 * PCI x 16 slot • 1 * Mini PCI-E
• Storage	• 6 * Serial ATA3 6Gb/s connectors support RAID 0, 1 & 10functions
• Audio	• Realtek ALC662 6-Channel HD Audio CODEC
• Ethernet LAN	• 2 * Realtek RTL8111EVL PCI-E LAN chip for Gigabit LAN
• USB	• Embedded 4 * USB 3.0 & 8 * USB 2.0/1.1

• Rear Panel I/O	<ul style="list-style-type: none"> • 2 * USB 3.0 & 4 * USB 2.0/1.1 ports • 2 * RJ-45 ports • 1 * Audio I / O port • 1 * VGA port • 1 * DP port • 1 * HDMI port • 2 * COM ports
• Internal I/O	<ul style="list-style-type: none"> • 2 * USB 3.0 & 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports • 1 * KB/MS header • CPU / Chipset / Chassis Fan connectors • 1 * GPIO header • 1 * 24-pin & 4-pin 12V ATX Power connector • 1 * TPM 1.2 header • 4 * COM header (COM6 for RS232/422/485) • 1 * CIR header • 1 * AUDIO header • 1 * Chassis Intrusion header
• BIOS	• AMI EFT 64MB SPI Flash ROM
• Certificate	• CE,FCC,RoHS,EuP
• Functional	• Digital Signage, Gaming Machine, POS Machine
• Temperature	<ul style="list-style-type: none"> • Operating within 0~50 centigrade • Storage within -20-85 centigrade
• Form Factor	• Mini ITX Form Factor(170mmx170mm)