




1419.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake !
- HBJC38AZ02 Series !



Part No.	– HBJC38AZ02 SERIES
BIOS	– AMI Flash ROM
CPU/Chipset	– Intel® Taigerlake-UP3 Soc Processor (i5-1145G7/default)
Memory	2* DDR4 3200MHz SO-DIMM up to 64GB
Graphics	Intel HD Graphics, shared memory 2 * DP (Max Resolution: 4096x2304@60Hz) 1 * HDMI 2.0 (Max Resolution: 4096x2160@60Hz)
Network	– 1 * Intel i219LM GbE – 1 * Intel i225V GbE
Storage	– 1 * M.2 M-key 2242/2280 (SATA/PCIe Gen4 x4 Interface support NVMe) – 1 * 2.5" SATA HDD (6Gb/s)
Expansion	– 1 * M.2-2230 E-Key (USB2.0/PClex1 for WiFi support CVNi) – 1 * M.2-3042/3052 B-Key (USB3.1/USB2.0/PCIe x1 for 4G&5G expansion) - 1 * SIM Card Adapter (Internal)
Rear Panel I/O	– 2 * USB 2.0 – 2 * USB 3.2 (Gen.2) – 1 * DP, 1 * HDMI – 2 * RJ45 (2.5Gbps/1.0 Gbps) – 1 * Line out, 1 * MIC combo – 2 * COM (TOP: co-lay GPÜIO, Bottom: Support RS 232) – 1 * DC Jack (Lock Type) – 3 * Antenna holes (Optional)

Front Panel I/O	– 1 * Power Button + LED – 1 * HDD LED – COM (By Model) – Intel LAN (By Model) – GPIO (8-bits IN & 8-bits OUT / by Model) – USB3.0 (by Model)
Power Source	– Adapter / AC 100~240V input / DC19V-90W – MB : DC 12~24V input
Compliance	– CE, FCC, LVD, RoHS,
Temperature	– Operating Temperature: -20 ~ 50° C (Under the condition of using M.2 interface SSD) (The test environment is closed and windless) – Storage Temperature: -20 ~ 70° C – Humidity : 40% ~ 60% RH (non-condensing)
Dimensions	– 185 (W) x 175 (D) x 60 (H) mm
OS Support	– Windows 11, Linux