



489.00 EUR

incl. 19% VAT, plus [shipping](#)

- Barebone !
- Intel N97 !
- 2x LAN !
- 3 Display support !

- Powered by Intel® N97 SoC Processor (formerly Alder Lake)
- High-Performance Memory: Supports DDR5 SO-DIMM
- 4K Display: Supports DP Alt Mode
- Storage & Expansion: 1 x M.2 E-Key, 1 x M Key
- Enhanced Security: TPM 2.0
- Dual 2.5GbE Ports for Reliable and High-Speed Networking Connections

SYSTEM	NUC
MB FORM FACTOR	Onboard Intel® Processor N97 (Formerly Alder Lake-N, TDP 12W)
CPU	Intel® SoC
CHIPSET	1 x DDR5 4800MHz, Single Channel SO-DIMM, up to 32GB
MEMORY	UEFI
BIOS	Yes
WAKE ON LAN	255 Levels
WATCHDOG TIMER	TPM2.0 (dTPM, Optional)
SECURITY	Lithium Battery
RTC BATTERY	Windows® 11 (64bit)
OS SUPPORT	Windows® 10 (64bit)
POWER	Linux
POWER REQUIREMENT	DC-in 12-19V
POWER ON MODE	60W Adapter: AC90~240V, DC12V/5.0A
DISPLAY	AT / ATX (Default) Mode
GPU	Intel® UHD Graphics

	2 x Type C DP1.4 (Max Resolution: 4096 x 2160@60Hz)
DP/HDMI	1 x DP1.4 (Max Resolution: 4096 x 2160@60Hz)
	1 x HDMI 2.0 (Max Resolution: 4096 x 2160@60Hz)
	Support 3 Displays
AUDIO	
CODEC	Realtek Audio Codec
LAN	
ETHERNET	2 x RJ45 for Intel® I226-V 2.5GbE
SYSTEM I/O	
	2 x RJ45
	1 x HDMI 2.0
	1 x DP 1.4
REAR PANEL I/O	2 x USB 3.2 Gen 2
	1 x DC-in (Lockable)
	2 x WIFI Antenna Holes (Optional)
	1 x GND Hold
	1 x Power Button
FRONT PANEL I/O	2 x USB 3.2 Type C support DP ALT mode
	1 x Combo Audio (Line out & Mic)
	1 x RS-232/422/485
EXPANSION	
M.2	1 x M-Key 2260/2280 (PCIe 3.0 x2/SATA III) Support NVMe
	1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1) Support CNVio
MECHANICAL	
MOUNTING	Wall + VESA mount
DIMENSIONS (W x D x H)	129.0 (W) x 109.4 (D) x 34.0 (H) mm
NET WEIGHT	0.56 KG
ENVIRONMENT & CERTIFICATION	
OPERATING TEMPERATURE	-20°C ~ 60°C (-4°F ~ 140°F)
CERTIFICATION	CE/FCC Class A
	LVD
	China RoHS
	CMRT Report
ESG DECLARATION	TSCA Declaration
	WEEE
	REACH